

2.4 Pickup

FAT TRUCK[®]
INDUSTRIAL OFF-ROAD UTILITY VEHICLES



Zeal Motor Inc.
101, rue de la Production
Cowansville, Quebec, Canada J2K 5H5
579.319.0060
sales@zealmotor.com
WWW.FATTRUCK.COM

2.4 Pickup

SPECIFICATIONS

PERFORMANCE		ENGINE		TIRES		OPTIONS	
Payload	2000 lb (905 kg)	Make	HATZ	Front & Rear	52 x 19 x 20 inches	Front winch	
Passenger capacity	4 (2 front + 2 rear)	Model	3H50TICD	Pressure	0.5 to 6 PSI (0.0035 to 0.42 kg/cm ²)	Additional battery	
Maximum speed on land	19 mph (30 km/h)	Number of cylinders	3 cylinders	FUEL SYSTEM			
Maximum speed on water	3.1 mph (5 km/h)	Displacement	89 cc ³ (1.46 L)	Capacity	19.5 US Gal (74 L)	Rear Hitch	
Maximum uphill & downhill	35°/ 70%	Horsepower @ 2400 RPM	56 hp (42 kW)	Average fuel autonomy	12 h	Front and rear shackles	
Maximum sidehill	22°/ 40%	Torque @ 1600 RPM	136 lb-ft (184 N-m)	STANDARD EQUIPMENT			
Turning radius	0°	Cooling System	Liquid cooled	Doors	Front	Studs for ice	
Base vehicle shipping weight	4200 lb (1900 kg)	ELECTRICAL		Operator seats	2 front seats with 3-points seat belts	Engine & hydraulic heater 110 V	
Ground pressure fully loaded	2 lb/pc ² (0.14 kg/cm ²)	Voltage	12 V	Lights	Front, brakes, position, flashers, dome	Canopy with openable windows, dome light	
SAFETY FEATURES		Alternator capacity	110 A	Horn	Electric	Heater / defroster	
ROPS	ISO 3471	Battery capacity	960 CCA	Ingress	Ladders with grab handles	Extra heater	
EPA / Emission	Tier 4 Final/Stage V	Battery type	AGM	Standard color	Black	Front windshield with wiper	
Brakes	Automatic safety brake	TRANSMISSION		Fire extinguisher	2.5 lb ABC	Custom color	
DIMENSIONS		Type	Hydrostatic	OPERATOR SEATS			
Height	91.5 in (2323 mm)	BRAKES		Bilge pump		Front roof rack	
Length	129 in (3283 mm)	Brakes	Positive deceleration through hydrostatic transmission	First aid kit		Rear roof rack	
Width	88 in (2236 mm)	Parking brakes	Brake disc applied, pressure released	Front and rear bumpers		Rear vinyl canopy	
Ground clearance	20.6 in (523 mm)	WARRANTY		Lockable fuel cap		Exterior mirrors	
CONTROLS		Limited 1 year / 1000 hours		Cup holders		Rear ROPS	
Controller	Microprocessor	(Which ever comes first)		Operator & Maintenance manual		Rear seats with safety belts	
Steering	Joystick					Directional light with remote control	
Display	Color display					Front, side and rear light LED bar	
						LED strobe light	
						Electronic inclinometer	
						Cold weather package	
						Ventilation fan	
						Storage box	
						Rear tailgate with ladder	
						Tow package	
						High flotation tires and rim	
						Wheel Pods™	
						Transportation trailer	
						Transportation rack	
						Amphibious trailer	

