

2.8 Wagon

FAT TRUCK[®]
INDUSTRIAL OFF-ROAD UTILITY VEHICLES



Zeal Motor Inc.

101, rue de la Production
Cowansville, Quebec, Canada J2K 5H5

579.319.0060

sales@zealmotor.com

WWW.FATTRUCK.COM

2.8 Wagon

SPECIFICATIONS

PERFORMANCE		ENGINE		TIRES		OPTIONS	
Payload	2200 lb (1000 kg)	Make	Hatz	Front & Rear	FAT TRUCK [®] LGP 1640 x 640 x 610	Front winch	
Passengers capacity	8 (2 front + 6 rear)	Model	1.95L Turbo diesel	Pressure	0.5 to 4.5 PSI (0.07 to 0.31BAR)	Additional battery	
Maximum speed on land	25 mph (40 km/h)	Emission standards	EPA Tier 4 Final EU Stage V	Pressure control	Automatic pressure control	Rear Hitch	
Maximum speed on water	3.1 mph (5 km/h)	Number of cylinders	4 cylinders	FUEL SYSTEM		Front and rear D-rings	
Maximum uphill & downhill	35°/ 70%	Displacement	119 po ³ (1.95 L)	Capacity	21 US Gal (80 L)	Studs for ice	
Maximum sidehill	22°/ 40%	Horsepower @ 2300 RPM	74 hp (55 kW)	Average fuel autonomy	12 h	Engine & hydraulic heater 110 V	
Turning radius	0°	Torque @ 1600 RPM	180 lb-ft (244 N-m)	STANDARD EQUIPMENT		Heater / defroster	
Shipping weight	5440 lb (2443 kg)	Cooling System	Liquid cooled	Doors	Lockable	Custom color	
Ground pressure fully loaded	1.6 lb/po ² (0.11 kg/cm ²)	ELECTRICAL		Operator seats	2 front seats with 3-points seat belts	Roof rack	
SAFETY FEATURES		Voltage	12 V	Lights	Front, brakes, position, flashers, dome	Exterior mirrors	
ROPS	ISO 3471	Alternator capacity	275 A	Horn	Electric	Back up camera	
EPA	Stage V	Battery capacity	960 CCA	Ingress	Front ladder with grab handles	Rear ROPS	
Brakes	Automatic safety brake	Battery type	AGM	Standard color	Red or white	Rear seats with safety belts	
DIMENSIONS		TRANSMISSION		Fire extinguisher	2.5 lb ABC	Directional light with remote control	
Height	101 in (2565 mm)	Type	Hydrostatic	4 sliding side windows		Front, side and rear light LED bar	
Length	146.5 in (3720 mm)	Final drive	Carbon fiber synchronous belts	Bilge pump		Extra heater	
Width	100 in (2540 mm)	BRAKES		Cup holders		4 corner LED beacon lights	
Ground clearance	20.7 in (526 mm)	Brakes	Positive deceleration through hydrostatic transmission	First aid kit		Electronic inclinometer	
CONTROLS		Parking brakes	Brake disc applied pressure released	Standard equipment		Hydraulic capstan and accessories	
Controller	Microprocessor	WARRANTY		Front and rear bumpers		Cold weather package	
Steering	Joystick	Limited 1 year / 1000 hours (Which ever comes first)		Lockable fuel cap		Ventilation fan	
Display	Color display			Operator & Maintenance manual		Tow package	
						Wheel Pods [™]	
						Transportation trailer	
						Transportation rack	
						Amphibious trailer	
						Air conditioning	
						Back-up alarm	
						Variable cooling fan for engine	
						4-way camera system	
						Hot sticks storage tubes	
						Blanket over engine compartment	
						Roof Hatch	
						Bluetooth radio	

