

8X8 Hauler

FAT TRUCK[®]
INDUSTRIAL OFF-ROAD UTILITY VEHICLES



Zeal Motor Inc.

101, rue de la Production
Cowansville, Quebec, Canada J2K 5H5

579.319.0060

sales@zealmotor.com

WWW.FATTRUCK.COM

8X8 Hauler



SPECIFICATIONS

PERFORMANCE		ENGINE		FRONT CAR STANDARD EQUIPMENT		FRONT CAR OPTIONS	
Payload Front Car	1000 lb (452 kg)	Make	Cummins	Lockable doors		Custom cab colors	
Payload Rear Car	4000 lb (1810 kg)	Model	F3.8 Turbo diesel	Ladder, steps, grab handles		Air conditioning	
Passengers	4 front	Emission standards	EPA Tier 4 final EURO Stage V	2 x Seats with 3-points seat belts		Rear seats with seat belts	
Maximum speed on land	25 mph (40 km/h)	Number of cylinders	4 cylinders	Lights (LED): Front, brakes, position, flashers, dome		Bluetooth radio with speakers	
Maximum speed on water	3.1 mph (5 km/h)	Displacement	232 in ³ (3.8 L)	LED beacon lights		Side working LED lights	
Maximum uphill & downhill	35° / 70%	Horsepower @ 2500 RPM	173 HP (129 kw)	Front LED bar		Searchlight with remote control	
Maximum sidehill	22° / 40%	Torque @ 1500 RPM	457 lb-ft (620 N-m)	Electric Horn		2 x Front forward facing seat on the back	
Turning radius	24 ft (7.3 m)	Cooling System	Liquid cooled	Heater / Defroster		Electric front Winch 12 000 lb	
Basic vehicle weight	13 000 lb (5910 kg)	FUEL SYSTEM		Back up camera 4 way camera system		Studded tires for ice	
Ground pressure loaded	1.9 psi (0.13 bar)	Capacity	45 US Gal (170 L)	Electronic Inclinometer		110V AC engine block & hydraulic tank heater	
SAFETY FEATURES		Driving range	186 miles (300 km)	Roof hatch		4 x Circulating fans	
ROPS	ISO 3471	Average fuel autonomy	12 h	Brush guard		Cold weather package:	
Brakes	Automatic safety brake	Urea tank	8.33 US gal (31.5 L)	Exterior mirrors		Front 6000 BTU heater for feet	
DIMENSIONS		POWERTRAIN		Lockable fuel cap		Rear diesel cab heater	
Height	111 in (2794 mm)	Type	Hydrostatic	Bilge pump		Diesel coolant heater	
Overall length	322 in (8179 mm)	Final drive	8 x Hydrostatic motors	Front bumper			
Width	100 in (2540 mm)	BRAKES		4 x Sliding side windows		REAR CAR STANDARD EQUIPMENT	
Ground clearance	25 in (635 mm)	Brakes	Positive deceleration through hydrostatic transmission	2 x D-rings		LED stops, signals, backup lights	
CONTROLS		Park brakes	Brake disc applied pressure released	Standard color: Red or White		Bilge pump	
Controller	Microprocessor	TIRES		LED rear light bar		Backup alarm	
Steering	Joystick	Front & Rear	FAT TRUCK® LGP 1640 x 640 x 610	First aid kit		Rear hitch	
Display	Rugged touch screen	Pressure	0.5 to 6 psi (0.07 to 0.41 bar)	Emergency Hammer		Tail gates with ladder	
ELECTRICAL		Pressure control	Presets and variable pressure control	Fire extinguisher 2.5 lb. ABC		8 x Tie downs	
Voltage	12 V	FRONT CAR OPTIONS		Operator & Maintenance manual		Wheel pods™	
Alternator capacity	150 A	REAR CAR STANDARD EQUIPMENT		Wheel pods™		2 x D-rings	
Battery capacity	2 x 930 CCA	FRONT CAR OPTIONS				REAR CAR OPTIONS	
Battery type	AGM	REAR CAR STANDARD EQUIPMENT				Fender tool box	
		REAR CAR STANDARD EQUIPMENT				Exterior storage box	
		REAR CAR STANDARD EQUIPMENT				WARRANTY	
		REAR CAR STANDARD EQUIPMENT				Limited 1 year / 1000 hours	
		REAR CAR STANDARD EQUIPMENT				(Which ever comes first)	

